

EAGLEEYE DIRECTOR II

HIGHLIGHTS

- ✓ Automatic People Tracking
- ✓ Inclusive Experience
- ✓ More Engaging And Less Stressful Meeting Experience
- ✓ Easy To Upgrade Existing Video Systems
- ✓ Remote Configuration Is Easy
- ✓ Smart Data Analytics
- ✓ Frame Speaker

ORDER NOW

 **+91 9810166450**

www.savivision.com

Vision for the next...



EAGLEEYE DIRECTOR II

About Eagleeye Director II

Meeting across sites is as natural as being in the same room now that presenters are seen up close without fumbling with technology. EagleEye Director II camera automatically zooms in on an active speaker without the use of a remote control or camera presets. EagleEye Director II takes video conferencing to the next level so meeting participants no longer have to worry whether they're in camera view or stop the conversation to grab the remote control. For larger meetings, two EagleEye Director II cameras can be connected via Cascading Mode to ensure every part of your meeting is in view. Now, 100% of your time in meetings is focusing on the bigger issue—solving critical business problems.

Benefits

More engaging and less stressful meeting experience with automatic camera technology that zooms in on an active speaker without anyone using a remote control

See nonverbal cues up close and maintain context of the room with single stream video of both the active speaker and everyone in the room

Measure return on investment with powerful data analytics for IT administrators*

Extend into larger rooms up to 10 m such as boardrooms, classrooms and assembly meeting spaces.

Easy to upgrade existing video systems for immersive-like meeting experience



Vision for the next...

EAGLEEYE DIRECTOR II

SPECIFICATION

PACKAGE INCLUDES:

- EagleEye Director II base, power supply and necessary cables
- EagleEye Director II base, power supply, necessary cables and one EagleEye IV
- EagleEye Director II base, power supply, necessary cables and two EagleEye IV cameras

COMPATIBLE CAMERAS

- 2x EagleEye™ IV 12X camera

COMPATIBLE POLYCOM VIDEO SYSTEMS

- RealPresence Group 300, 310, 500, 550 and 700**
- Poly G7500

COMPATIBLE MICROSOFT SYSTEMS

- Certified for Skype for Business
- Microsoft Surface Hub and Hub 2
- Certified for Microsoft Teams Rooms

RECOMMENDED ROOM SIZE

- Participants should be within 33 feet (10 m) of each EagleEye Director II
- Performance may vary in different room configurations



MODES

- Frame speaker
- Frame group

CONNECTIONS

- 1 x mini-HDCI out to video system
- 2 x USB 2.0
- 1 x 3.5 mm stereo line-in
- 1 x HDMI in
- 1 x HDMI out

ENVIRONMENTAL SPECIFICATIONS

- Operating temperature: 0°—40° C ambient
- Operating humidity: 10—90%
- Storage temperature: -40°—70° C
- Non-operating humidity: 5%—95%, non-condensing
- Altitude: 5,000 meters operational, 10,668 meters non-operational (transportable)
- Will operate in florescent lighting environments worldwide

PHYSICAL CHARACTERISTICS

- Base box with vertical array: 11.14" x 21.57" x 5.5" (H x W x D)
- 283 mm x 548 mm x 140.5 mm (H x W x D)
- Weight: 4.7kg with two EagleEye IV cameras

ELECTRICAL

- Auto sensing power supply for full-duplex
- Typical operating voltage/power : - 100 — 240VAC, 50/60Hz
Output 12V@5A