

POLY G200

HIGHLIGHTS

- ✓ Sharp, rich and reliable video
- ✓ Minimize meeting disruptions from background noise with advanced audio technology
- ✓ Affordable video collaboration device with uncompromised audio and video quality
- ✓ Bluetooth 4.0
- ✓ Authenticated access to admin menus, web interface

ORDER NOW

 **+91 9810166450**

www.savivision.com



Vision for the next...

POLY G200

SPECIFICATION

PACKAGE INCLUDES

- G200 codec
- EagleEye Mini camera or EagleEye Cube USB camera
- Poly Studio Microphone
- Bluetooth® Remote control (for G200)
- Cable bundle

VIDEO STANDARDS AND PROTOCOLS

- H.264, H.264 High Profile, H.239
- H.264 video error concealment

VIDEO INPUT

- 1 x USB
- 1 x HDMI

VIDEO OUT

- 2 x HDMI

PEOPLE VIDEO RESOLUTION ENCODE

- 1920x1080, 30fps (HD 1080p)
- 1280x720, 30fps (HD 720p)
- 640x360, 30fps
- 320x180, 30fps

CONTENT SHARING

- 1 x HDMI input
- Polycom Content App support



AUDIO INPUT

- 1 x Polycom Studio Expansion microphone
- 1 x HDMI
- 1 x USB

AUDIO OUTPUT

- 1 x HDMI
- 1 x USB

OTHER INTERFACES

- 2x USB 2.0
- 1x USB-C1
- Bluetooth 4.0

AUDIO STANDARDS AND PROTOCOLS

- 48KHz Siren LPR
- 16 kHz bandwidth with G.722.1
- 32 kHz bandwidth with G722.1C
- 8 kHz bandwidth with G.711
- 48 kHz bandwidth with G.719

PEOPLE VIDEO RESOLUTION DECODE

- 1920x1080, 30fps (HD1080p)
- 1280x720, 30fps (HD720p)
- 1280x768, 30fps (WXGA)
- 1024x768, 30fps (XGA)
- 800x600, 30fps (SVGA)
- 640x480, 30fps (VGA)
- 640x360, 30fps
- 320x240, 30fps (QVGA)
- SIF (352 x 240), 30fps
- 1024x576, 30fps (w576p)
- 768x448, 30fps (w448p)
- 576x448, 30fps (448p)
- 512x288, 30fps (w288p)

NETWORK

- IPv4 support
- 1 x 10/100/1G Ethernet
- H.323 or SIP up to 4Mbps
- Polycom Lost Packet Recovery (LPR) technology
- Dynamic Bandwidth Allocation

SECURITY

- Media Encryption (H.323, SIP):
AES-128, AES-256
- H.235 support
- Authenticated access to admin menus, web interface
- PKI/Certificate Management:
- TLS 1.2, 1.1, 1.0 - Self-signed and CA-signed certificate support

OPTIONS

- EagleEye IV USB camera
- Poly Studio

CONTENT VIDEO RESOLUTION

- Input (Through 1 x HDMI)
 - WUXGA (1920 x 1200)
 - HD (1920 x 1080)
 - HD (1280 x 720)
 - WXGA (1280 x 768)
 - XGA (1024 x 768)
 - SVGA (800 x 600)
- Receive
 - HD (1920 x 1080)
 - HD (1280 x 720)
 - XGA (1024 x 768)
- Transmit
 - HD (1920 x 1080)
 - HD (1280 x 720)
- Content frame rate
 - 5–30 fps

ELECTRICAL

- Typical operating voltage/power
 - 24VA @ 230V @ 50/60 Hz
 - 24VA @ 120V @ 60 Hz
- Typical BTU/h
 - 51

PHYSICAL CHARACTERISTICS

- G200 base box
 - 320mm (L) x 235mm (W) x70mm (H)
 - 1.3kg

ENVIRONMENTAL SPECIFICATION

- Operating temperature
 - 0 to 40 °C
- Operating humidity
 - 20 to 80%
- Non-operating temperature
 - 20 to 70 °C
- Non-operating humidity (non- condensing)
 - 5 to 95%
- Maximum altitude
 - 5000m

savi
Vision for the next...