

POLY STUDIO X30



HIGHLIGHTS

- ✓ 4K UltraHD video
- ✓ Innovative acoustic chamber design.
- ✓ Poly NoiseBlockAI and Acoustic Fence smart audio filtering technologies.
- ✓ Seamless native experience on leading cloud video services
- ✓ Poly DirectorAI smart camera technology

ORDER NOW

 **+91 9810166450**

www.savivision.com

Vision for the next...



POLY STUDIO X30

About Poly Studio X30

Make your video conferencing easier and more powerful. The Poly Studio X30 includes legendary audio and video performance in a simple all-in-one video bar. Offer true meeting equality with pinpoint-accurate automatic framing and tracking modes, distraction-free audio technology, and life-like 4K UltraHD video. There's no PC required, either: Cloud video apps are built right in, offering familiar controls, and support for the leading cloud video services. And with Poly Lens, deployment, management and analytics are a breeze for IT.

Benefits

Get any small room up and running in minutes, with a simple setup process and all-in-one design.

Catch even the smallest details with its 4K UltraHD 120-degree FOV camera.

Enjoy legendary audio from Poly, with crisp, room-filling sound made possible by an innovative acoustic chamber design.

Enjoy a seamless native experience on all the leading cloud video apps — no PC or separate gateway required.

Ensure everyone is seen clearly with Poly DirectorAI's pinpoint-accurate automatic framing technologies.

Keep distracting noises and side conversations from interrupting your meetings with Poly NoiseBlockAI and Acoustic Fence technologies.



Vision for the next...

POLY STUDIO X30

SPECIFICATION

PACKAGE INCLUDES:

- Poly Studio X30
- Power supply
- HDMI cable
- Ethernet cable
- Monitor clamp
- Privacy cover

VIDEO STANDARDS AND PROTOCOLS

- H.264 AVC, H.264 High Profile, H.265, H.239

VIDEO INPUT

- 1x HDMI

VIDEO OUT

- 1x HDMI
- Touch display compatible

PEOPLE VIDEO RESOLUTION

- 4K, 30 fps (TX and RX) from 2048 Kbps
- 1080p, 60 fps from 1740 Kbps
- 1080p, 30 fps from 1024 Kbps
- 720p, 60 fps from 832 Kbps
- 720p, 30 fps from 512 Kbps

CAMERA

- 121° DFOV, 110° HFOV
- 5x digital zoom
- UHD 2160p (4K) capture resolution
- Automatic meeting experience powered by Poly DirectorAI including group framing and speaker framing



CONTENT SHARING

- Apple Airplay
- Miracast
- HDMI input
- Whiteboarding

CONTENT VIDEO RESOLUTION

- Input
 - UHD (3840 x 2160)
 - HD (1920 x 1080p)
 - WSXGA+ (1680 x 1050)
 - UXGA (1600 x 1200)
 - SXGA (1280 x 1024)
 - WXGA (1280 x 768)
 - HD (1280 x 720p)
 - XGA (1024 x 768)
 - SVGA (800 x 600)
- Output
 - UHD (3840 x 2160)
 - WUXGA (1920 x 1200)
 - HD (1920 x 1080)
 - WSXGA+ (1680 x 1050)
 - SXGA+ (1400 x 1050)
 - SXGA (1280 x 1024)
 - HD (1280 x 720)
 - XGA (1024 x 768)
- Content frame rate
 - 5–60 fps (up to 4K resolution at 15 fps in call)

AUDIO

- Poly NoiseBlockAI technology
- Poly Acoustic Fence technology

MICROPHONES

- Four MEMS microphones
- Up to 15 ft of microphone pickup range

AUDIO OUTPUT

- 1x HDMI
- Single speaker
 - Power Handling (RMS) 3W
 - Power Handling (MAX) 5W
 - Sensitivity 80dB

OTHER INTERFACES

- 1x USB-A (3.0)
- 1x USB-C
- Bluetooth 5.0*
- WiFi 802.11a/b/g/n/ac (MIMO) Multi-channel Concurrency*

Vision for the next...

AUDIO STANDARDS AND PROTOCOLS

- 22 kHz bandwidth with Polycom Siren 22 technology
- 20 kHz bandwidth with G.719 (M- Mode) and Polycom Siren 22 technology
- 14 kHz bandwidth with Polycom Siren 14 technology, G.722.1 Annex C
- 7 kHz bandwidth with G.722, G.722.1
- 3.4 kHz bandwidth with G.711, G.728, G.729A

NETWORK

- IPv4
- IPv6
- 1x 10/100/1G Ethernet
- Auto-MDIX • H.323 and/or SIP up to 6 Mbps in Poly App video mode
- Polycom Lost Packet Recovery (LPR) technology
- Dynamic bandwidth allocation
- Reconfigurable MTU size
- Web proxy support—basic, digest, and NTLM

SECURITY

- Media Encryption (H.323, SIP): AES-128, AES-256
- H.235.6 support
- Authenticated access to admin menus, web interface, and APIs
- BFCP
- Local account password policy configuration
- Security profiles
- Local account and login port lockout
- Secure defaults
- Remote logging with support for TLS
- Active directory external authentication

OPTIONS

- VESA and wall mount kit
- Stand
- Poly TC8
- Poly TC10
- Poly Bluetooth remote control
- Poly Trio
- Inverted mount kit
- TAA, JITC and no radio versions available

INTEROPERABILITY

- Zoom Certified
- Microsoft Teams Certified
- Google Meet Certified
- All cloud service providers through Poly Video App mode
- USB Device Mode
- Support for native 3rd party applications includes Zoom, Microsoft Teams, Google Meet, BlueJeans, Dialpad, GoToRoom, RingCentral and Tencent (China only)

DIGITAL SIGNAGE

- Raydiant
- Appspace

ELECTRICAL

- Auto sensing power supply
- Typical operating voltage/power
 - 37 VA @ 120 V @ 60 Hz
 - 37 VA @ 230 V @ 50/60 Hz
- Typical BTU/h: 65

ENVIRONMENTAL SPECIFICATION

- Operating temperature: 0 to 40 °C
- Operating humidity (non-condensing): 15 to 80%
- Non-operating temperature: -40 to 70 °C
- Non-operating humidity (noncondensing): 5 to 95%
- Maximum altitude: 16,000 ft

AUDIO

- Poly NoiseBlockAI technology
- Poly Acoustic Fence technology

MICROPHONES

- Four MEMS microphones
- Up to 15 ft of microphone pickup range

AUDIO OUTPUT

- 1x HDMI
- Single speaker
 - Power Handling (RMS) 3W
 - Power Handling (MAX) 5W
 - Sensitivity 80dB